

Ihr Spezialist für
Mess- und Prüfgeräte



Agilent Technologies

Authorized Distributor

Agilent 33502A 2-channel 50 Vpp Isolated Amplifier

Data Sheet



- Full-power BW 100kHz @ 50Vpp
- Small-signal BW > 300kHz
- Slew Rate 20V/μs min.
- THD+N < 0.01% @ 10kHz, 40Vpp.
- Output drive 200mA max.
- Isolation Floats ±42Vpk to earth

The Agilent 33502A is a dual-channel, high voltage output amplifier. It has an isolated analog front end with up to 50 Vpp (± 25 V) output voltage range. It is also a very low-distortion amplifier with < 0.01% @ 10 kHz and 40 Vpp. The 33502A is designed to work as a companion for function generators to offer low-distortion, higher voltage outputs.

The 33502A has a fully isolated front end, which offers superior 5X voltage amplification to other amplifiers. You can independently configure input coupling (AC | DC) and input impedance (50Ω | 1MΩ) to match your circuit. The input path can also be switched from amplified to direct (unamplified) without removing or connecting cables.

The 33502A, in a 2 unit, half-rack mechanical form factor, fits well on both your bench and in your test system. It also is configured with LAN (LXI Class-C compliant) and USB interfaces to meet your computer IO needs.

The 33502A provides both a programmable interface and a softkey-driven front panel for flexibility in configuring.

The 33502A is compatible with existing Agilent function/arbitrary waveform generators including the 33120A, 33210A, 33220A, and 33250A. It can also be used to amplify signals from non-Agilent function and arbitrary waveform generators.



Table 1.

Feature	Characteristic
General	
Number of channels	2
Channel to channel ground connection	Not connected in BYPASS ON. Connected with both channels OFF or in Gain of 5x
Floating Voltage	± 42 Vpk to earth
Input Configuration & Specification	
Input Coupling	
AC Coupling	Programmable
DC Coupling	Default, Programmable
Input Impedance	
1M Ω	Default, Programmable
50 Ω	Programmable
Input Voltage Range	
Maximum Voltage Range	± 5 Vpk for gain of 5x, ± 30 Vpk for bypass
Damage Level	± 10 Vpk for 50 Ω input ± 35 Vpk for 1 M Ω input
Input Path	Programmable gain of 5x, bypass (1x), or off state
Input Gain 5X	5X, Fixed, Non-Inverting
Gain Accuracy ²	$\pm 0.1\%$ @ 1KHz
Flatness DC coupling ¹	0.1% : dc - 10KHz 1% : dc - 40KHz 5% : dc - 100KHz
Flatness AC coupling ¹	0.1% : 30Hz - 10KHz 1% : 10Hz - 40KHz 5% : 3Hz - 100KHz
Small Signal Bandwidth ¹	> 300 KHz (-3db)
Full Power Bandwidth ¹	100KHz @ 50Vpp output
Input Bypass	
Bandwidth for 50 Ω system	> 300 MHz (-3db)
Maximum Current	0.2 Apk
Noise	
Input referred noise	< 40nV/ rt-Hz @ 1kHz
Output Configuration & Specification	
Output Current	200mA. (150mA for continuous output from -8V to +8V)
DC Output Resistance	< 2 Ω
Max Output Level ¹	± 25 Vpk
Output DC Offset	< 10mV
Output Slew Rate ¹	> 20V/us
THD + N ¹	< 0.01% @ 10kHz, 40 Vpp
Aberrations ¹	< 5% for waveforms with < 3V input step or non slewing output

¹For all loads >250 ohms and <400 pF of capacitance²Measured with ≥ 1 Mohm load and 1 Mohm input selection.

Table 1 (cont'd).

Feature	Characteristic
Transition time ¹ (Final value ±1% of step size)	2.5uSec+ 50nSec/volt of output step
Channel to channel isolation for gains of 5x	> 75dB
Capacitive Load for no oscillation	< 1 nF
Output Protection	Continuous short circuit protection
	Thermal overload shutdown.
	Over temperature status flag.

¹For all loads >250 ohms and <400 pF of capacitance.

Table 2

General Characteristics	
Power Supply	100V/120V/ 220V / 240V ± 10%
Power Line Frequency	50–60 Hz ± 10%, 400 Hz ± 10%.
Power Consumption	100 VA peak (typical value depends on configuration and load)
Operating Environment	Full accuracy for 0 °C to 55 °C Full accuracy to 80% R.H. at 40°C Non–condensing
Storage Temperature	–40 °C to 70 °C
Operating Altitude	Up to 3000m
Bench Dimensions (WxHxD)	261.2mm x 103.8mm x 303.2mm
Weight	3.1 kg (6.8 lbs)
Safety	Complies with European Low Voltage Directive and carries the CE-marking
	Conforms to UL 61010-1, CSA C22.2 61010-1, and IEC 61010-1:2001
EMC	Complies with European EMC Directive for test and measurement products. - IEC/EN 61326-1 - CISPR Pub 11 Group 1, class A - AS/NZS CISPR 11 - ICES/NMB-001
	Complies with Australian standard and carries C-Tick mark This ISM device complies with Canadian ICES-001. Cet appareil ISM est conforme à la norme NMB-001 du Canada
Acoustic Noise	Normal operating mode: SPL 35db(A)
Display	4.3" Color TFT WQVGA (480x272), LED backlight
Remote Interfaces	10/100Mbit LAN USB 2.0 Standard
Language	SCPI – 1994.0, IEEE–488.2
LXI Compliance	LXI Class C, Version 1.0
Number of Channels	2
Channel to channel ground connection	Not connected in BYPASS ON. Connected with both channels OFF or in Gain of 5x
Floating Voltage	±42 Vpk to earth

Faxantwort 07121 / 51 50 10

An: dataTec GmbH
Ferdinand-Lassalle-Str. 52
72770 Reutlingen
Tel.: 07121 / 51 50 50

Absender:

.....
Firma

.....
Name, Vorname

.....
Abteilung

.....
Straße

.....
PLZ/Ort

.....
Telefon

.....
Telefax

.....
E-Mail

.....
Firmenstempel/Datum/Unterschrift

Testgeräte-Service

Bitte setzen Sie sich mit mir schnellstmöglich in Verbindung. Ich möchte Ihren Testgeräte-Service in Anspruch nehmen und folgendes Gerät testen:

Produkt:



B2B-Online-Shop



Unverbindliche Beratung vor Ort

Sie haben eine Wunschliste für Ihr Labor oder für Ihren Arbeitsplatz? Eine besondere Anwendung oder Messung? Ihnen helfen wir gerne bei der Auswahl der geeigneten Messmittel und beraten Sie kompetent vor Ort. Vereinbaren Sie telefonisch einen Termin!

- Ja, ich möchte eine **Beratung vor Ort**
- Mein Wunschtermin:



Besuchen Sie unseren B2B-Online-Shop unter www.datatec.de

- übersichtliche Menüführung und Produktpräsentation
- über 1500 Produkte an Mess-, Netz-, Prüf- und Thermografiegeräten
- tagesaktuelle Preise und Promotions
- Onlinerabatt bei Bestellung
- Lieferung Frei Haus bei Bestellungen im Onlineshop
- direkte Angebotsanfrage von der aufgerufenen Produktseite aus
- komfortable Preisanfrage für Bildungseinrichtungen
- Firmen- bzw. personalisierter Login
- immer die neuesten Informationen
- einfacher Datenblatt-Download
- Testgeräteanforderung
- Firmware-, Software- und Demosoftware-Download