

Ihr Spezialist für  
Mess- und Prüfgeräte



## Keysight Technologies

Using a Wideband AWG to Optimize Data Throughput with  
Multi-Level Signaling Techniques

Application Brief



## Overview and motivation

Increasing the data throughput on high-speed digital interfaces can be accomplished in at least three ways:

1. Using multiple parallel signals
2. Increasing the symbol rate
3. Using higher order modulation schemes that carry more than 1 bit per symbol (such as NRZ)

Traditionally, #1 and #2 are used because NRZ data transmission is very well understood and can be realized in a cost-effective way, both on the transmit side as well as the receive side. However, there are limitations.

Using a large number of parallel signals requires a higher pin-count on chips and more traces on backplanes, cables and boards, which makes the overall solution more expensive and eventually impractical.

Increasing the symbol rate works well up to a certain point. But board traces have significant attenuation at higher frequencies. Depending on the length of the trace, increasing the symbol rate beyond ~32 Gbaud is very difficult. For technologies such as chip-on-glass used in smart-phone displays, the threshold is at even lower symbol rates of 1 to 2 GBaud.

Using a higher order modulation scheme has the advantage that more than 1 bit per symbol can be transmitted without increasing the bandwidth requirement. The spectrum plots below show that the data rate can be doubled without increasing the occupied bandwidth.






Figure 1: Spectrum of 6 Gbit/s NRZ,

6 Gbaud PAM4 (=12 Gbit/s),

12 Gbit/s NRZ

(all three data signals are raised cosine filtered with  $\alpha = 0.35$  in order to limit the bandwidth)

## Effect of transition times in PAM4

Unlike NRZ, where the transition time of the data signal does not generate significant horizontal eye closure, this is very different in PAM4. Therefore, even with “clean” signals (i.e. no jitter), there is a certain amount of **switching jitter** dependent on the rise and fall time of the signal. The two figures below illustrate the effect. The rise and fall times are normalized to 1 and assumed to be cosine shape, i.e. with minimum bandwidth. The dashed lines indicate the decision thresholds; the dotted lines indicate the amount of switching jitter.




Figure 2: transitions of NRZ and PAM4 signals showing the amount of switching jitter

The PAM4 graph shows that the **switching jitter affects the outer two eyes more than the center eye** – assuming that the decision thresholds are centered within the eye. The PAM4 diagram also shows that the **switching jitter is approximately equal to the 20/80 rise time of the signal**.

The following two screen shots with real signals confirm this rule-of-thumb. They show a 6 GBaud PAM4 signal with transition times of 22 picoseconds (ps) and 52 ps respectively. The red lines with the arrows show the amount of switching jitter. As shown in the scope measurements, the switching jitter matches quite well with the transition times.




Figure 3: Two PAM4 signals at 6 GBaud with different transition times

## Dealing with bandwidth limited channels

Switching from NRZ to PAM4 is often motivated by a bandwidth limitation of the channel (and/or the transmitter and receiver).

In the radio frequency (RF) world this is a very common problem because using excess bandwidth in a frequency division multiplex environment causes distortions in a neighboring channel. In order to limit the bandwidth of a digitally modulated signal, a pulse-shaping filter is applied to the baseband signal. Typical pulse shaping filters include raised-cosine or root-raised-cosine. The trade-off between occupied bandwidth and wide eye-opening of the time-domain signal can be controlled using the roll-off coefficient of the filter. The two plots below show the frequency response on a linear scale and the step response with different roll-off coefficients.




Figure 4: frequency response and step response of a raised cosine filter

With  $\alpha = 0.05$ , the occupied bandwidth is the most narrow (“brickwall filter”), but the step response shows significant ringing. With  $\alpha = 1$ , the occupied bandwidth is larger (still less than 2x the symbol rate), but the step response has almost no overshoot. The following two examples show 32 GBaud PAM4 signals with two different raised cosine filter coefficients: 0.1 and 1.0.




Figure 5: 32 GBaud PAM4 signal, raised cosine filtered with  $\alpha = 0.1$  and  $\alpha = 1.0$  respectively

Both signals can be decoded with similar error vector magnitude (EVM), but the occupied bandwidth is very different between the two, as shown in the following spectrum plots:




Figure 6: Spectrum of 32 GBaud PAM4 signal, raised cosine filtered with alpha = 0.1 and 1.0, respectively

### Channel embedding and de-embedding

Another benefit of using a high-speed AWG for generating PAM4 signals is the possibility to embed or de-embed the behavior of a channel. The characteristic of the channel can either be supplied by providing its S-parameters or it can be measured in-system. In the AWG, the waveform is digitally pre-distorted to include the frequency and phase response of the channel or its inverse.

The following screenshots show a clean PAM4 signal as well as the same signal with the S-parameters of a 522 mm long trace embedded and de-embedded.




Figure 7: Clean 2 GBaud PAM4 signal,

with channel embedded,

with channel embedded

## Non-equidistant voltage levels

For optical applications, it is often necessary to generate PAM4 signals with non-equidistant voltage levels if the external amplifier and the Mach-Zehnder modulator is used beyond their linear operating range.

The traditional method of generating a PAM4 signal is to passively combine two NRZ signals with an amplitude ratio of 2:1 to generate equidistant voltage levels. By changing the amplitude ratio, the height of the middle eye can be altered, but the height of the upper and lower eye always remain the same.




Figure 8: Generating PAM4 signals using two NRZ generators

When generating a PAM4 signal with a high-speed AWG, there is no such limitation – an arbitrary relationship of the four voltage levels can be realized. An example is shown in the following screenshot.




Figure 9: 16 GBaud PAM4 signal with non-equidistant voltage levels

## Higher order PAM modulations

Generating more than 4 discrete levels (e.g. PAM8, PAM16, etc.) is of course possible as well, but in order to gain an additional bit per symbol, the number of discrete levels has to be doubled, which requires significantly larger signal-to-noise ratio. Therefore, a significantly larger number of levels are rarely used.




Figure 10: 4 GBaud PAM4, PAM8 and PAM16 signals

Ihr Spezialist für  
Mess- und Prüfgeräte



## Adding distortions

Testing the margins of a receiver requires that the generator can add distortions to the signal, such as variable transition times, jitter, noise, inter-symbol interference (ISI) and duty cycle distortion (DCD). High-speed AWGs can add all of these distortions without any additional hardware such as ISI traces. Below are a few examples of distortions added to PAM4 signals:






Figure 11: PAM4 signal – clean,



with slow transition times,



with added jitter






Figure 12: ...with added ISI,



with DCD,



with jitter, ISI and noise

## Conclusion

High speed AWGs, such as the new Keysight M8195A are very well suited to generate PAM4 signals up to 32 GBaud including the necessary parameter changes, such as:

- Variable transition times
- Various pulse shaping filters
- Adding distortions, including:
  - Jitter
  - Noise
  - DCD
  - ISI
- Embedding and de-embedding S-parameters
- Generating PAMx signals with non-equidistant voltage levels



Using an AWG for signal generation provides greater flexibility than traditional NRZ generators – independent of which direction the technology goes.

Ihr Spezialist für  
Mess- und Prüfgeräte



# MESSBAR MEHR AUSWAHL.

MIT AKTUELLEN PREISEN, PRODUKTHIGHLIGHTS UND ZUBEHÖR.  
DER B2B-ONLINESHOP.



**STARKE MARKEN. HÖCHSTE PRODUKTVIELFALT. BESTE QUALITÄT.**

Schnell und bequem online bestellen – bei dataTec ist das möglich. Bei uns finden Sie die perfekte Lösung für ihre vielfältigen Anforderungen.

Wir bieten eine **unschlagbare Auswahl** an Mess- und Prüfgeräten namhafter Hersteller. Diese reicht von Arbiträr-Funktionsgeneratoren über Logikanalysatoren bis hin zu Stromversorgungen und Stromzangen oder **Oszilloskopen bis 100 GHz Bandbreite**. Hohe Lagerkapazität und kurze Wege sorgen dafür, dass die gewünschte Ware ganz schnell bei Ihnen ist. Bundesweit meist innerhalb eines Tages.

**Mehr Klicks, mehr Vorteile:**

- Mehrere tausend Mess- und Prüfgeräte
- Tagesaktuelle Preise und Promotions
- Warenkorbrabatt bei Onlinebestellung
- Versandkostenfrei (ab € 50,-)
- Datenblatt-Download
- uvm.

Angebotsanfrage oder Bestellung unter:

**[www.datatec.de](http://www.datatec.de)**

